

# Certificate of Constancy of Performance

This is to certify that:

Rockwool Ltd  
Wern Tarw Road  
Pencoed  
Bridgend  
CF35 6NY  
United Kingdom

Holds Certificate Number: 0086-CPR-636615

In respect of:

**EN 14303:2009+A1:2013**

**With conformity established according to EN 13172:2012**

## Product description

**Mineral wool thermal insulation products for building equipment and industrial installations**

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 are applied and that the product fulfils (products fulfil) all the prescribed requirements set out above. This certificate remains valid as long as the test methods and/or factory production control requirements included in the harmonised standard(s), used to assess the performance of the declared essential characteristics, do not change and the products(s), and the manufacturing conditions in the plants(s) are not modified significantly.



For and on behalf of BSI, a Notified  
Body for the above Regulation  
(Notified Body Number 0086):

\_\_\_\_\_  
Gary Fenton, Global Product Certification Director

First Issued: 29/07/2015

Latest Issue: 29/07/2015

Page: 1 of 2

...making excellence a habit.™

# Certificate of Constancy of Performance

No. 0086-CPR-636615

**EN 14303:2009+A1:2013 - Thermal insulation products for building equipment and industrial installations. Factory made mineral wool (MW) products.**

## Product information: Euroclass A1

All un-faced mineral wool insulation products for building equipment and industrial installations, as detailed in the Rockwool Technical File; within the following parameters:

% Binder content	Density range
≤ 5.0	19 - 220 kgm <sup>3</sup>

All mineral wool insulation products for building equipment and industrial installations with aluminium foil facing on one side, as detailed in the Rockwool Technical File; within the following parameters:

% Binder content	Density range
≤ 5.0	≤ 220 kgm <sup>3</sup>

## Product information: Euroclass A2

All concentrically wound pipe section mineral wool insulation products for building equipment and industrial installations with aluminium foil facing on one side, as detailed in the Rockwool Technical File; within the following parameters:

Diameter	% Binder content	Density range
$D_0 \leq 300\text{mm}$	≤ 4.5	140 kgm <sup>3</sup>
$D_0 > 300\text{mm}$	≤ 5.0	≤ 220 kgm <sup>3</sup>

$D_0$  = Outer diameter

First Issued: 29/07/2015

Latest Issue: 29/07/2015

Page: 2 of 2

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.